


LED String Work Light



Product Features


- 5 lights or 10 lights per bunch for option. Suitable to different demand of distant.
- Light heads spaced 10 feet/3mts apart, same to traditional string work light.
- Available in 18AWG/16AWG/12AWG power wire.
- Each lamp with metal hook, flexible for easy intallation.
- Misty PC cover protect eyes better, anti-dazzle design.
- Over 50000 hours lifetime and offer 5 years warranty.
- ETL/cETL/CE/RoHS certificates.



Option 1: It has 5 LED light heads and comes with a 50ft AC cord, Light heads spaced 10 feet/3mts apart
 Option 2: It has 10 LED light heads and comes with a 100ft AC cord, Light heads spaced 10 feet/3mts apart




Milky cover with 270° beam angle, soft light



Flexible hook, easy installation




The connector with waterproof cover




1-15P & 1-15R plug and 5-15P & 5-15R plug are available

Item NO.	Watt	Lamp Quantity	Lumen	Length	CCT	Voltage	CRI	PF	Beam Angle	Awg Size	IP Rating
RMS-H5-4-40W	40W	5pcs	5000LM±10%	50ft	3000K 4000K 5000K 5700K 6500K	AC100V-277V, 50-60Hz	>80	>0.9	270°	18/16/12	IP65
RMS-H5-4-80W	80W	10pcs	10000LM±10%	100ft							

Test Data of Maximum Linkable Quantity			
Working Condition: Input voltage is AC120V, each light head spaced 10ft apart, the maximum quantity for fixture's plug to link another fixture's socket, without extra power cord			
AWG Size:	Model Number:	40W, same power	80W, same power
18AWG		10 pieces	5 pieces
16AWG		10 pieces	7 pieces



Color Temperature



Operation Temperature



Expected life over 50,000 hrs




5 Year Warranty

Product Features


- 5 lights or 10 lights per bunch for option. Suitable to different demand of distant.
- Light heads spaced 10 feet/3mts apart, same to traditional string work light.
- Available in 18AWG/16AWG/12AWG power wire.
- Each lamp with metal hook, flexible for easy intallation.
- Misty PC cover protect eyes better, anti-dazzle design.
- **Come with metal cage, more safety and durable.**
- Over 50000 hours lifetime and offer 5 years warranty.
- ETL/cETL/CE/RoHS certificates.



Option 1: It has 5 LED light heads and comes with a 50ft/ AC cord, Light heads spaced 10 feet/3mts apart
 Option 2: It has 10 LED light heads and comes with a 100ft AC cord, Light heads spaced 10 feet/3mts apart




With metal cage, better protection on the light source



Flexible hook, easy installation




The AC plug with waterproof cover




1-15P & 1-15R plug and 5-15P & 5-15R plug are available

Item NO.	Watt	Lamp Quantity	Lumen	Length	CCT	Voltage	CRI	PF	Beam Angle	Awg Size	IP Rating
GLMS-H5-4B-40W	40W	5pcs	5000LM±10%	50ft	3000K 4000K 5000K 5700K 6500K	AC100V-277V, 50-60Hz	>80	>0.9	270°	18/16/12	IP65
GLMS-H5-4B-80W	80W	10pcs	10000LM±10%	100ft							

Test Data of Maximum Linkable Quantity			
Working Condition: Input voltage is AC120V, each light head spaced 10ft apart, the maximum quantity for fixture's plug to link another fixture's socket, without extra power cord			
AWG Size:	Model Number:	40W, same power	80W, same power
18AWG		10 pieces	5 pieces
16AWG		10 pieces	7 pieces



Color Temperature



Operation Temperature



Expected life over 50,000 hrs



5 Year Warranty