













DESCRIPTION

LED Temporary Work Fixture is ideal for a wide range of construction jobsite and maintenance activates with features designed to fit any application. Long lifespan, superior energy efficiency up to 75%, quick install, plug-n-play instant operate, portable, durable temporary lighting.

KEY FEATURE

- 360°Omni-directional lighting.
- Ultra-bright: 120lm/W.
- Come with 5-foot 18AWG cord and 120V plug.
- · Built-in socket, can be linked one by one.
- Suitable for dry and damp location.
- · Portable hook, easy to carry and quick install.



- Ventilation air-flow heat sink design for better heat dissipation.
- High quality led driver to ensure stable working situation.
- Waterproof rubber design for better waterproof performance.
- Operating temperature: -40 $^{\circ}\mathrm{C}/\text{-40}^{\circ}\mathrm{F}$ to $60\,^{\circ}\mathrm{C}/\text{140}^{\circ}\mathrm{F}$.

SPECIFICATION

Item NO.	Watt	Total Lumens	Dimension	ССТ	Input Voltage	CRI	Power Factor	Operating Temperature	Beam Aangle
GLMS-H5-9-60W	60W	7200LM	Ø130*H223mm						
GLMS-H5-9-100W	100W	12000LM	Ø132*H273mm	3000K~6500K	AC100-277V, 50-60Hz	>80	>0.9	-40°C to 60°C	360°
GLMS-H5-9-150W	150W	18000LM	Ø132*H323mm						

Test Data of Maximum Linkable Quantity									
Working Condition: Input voltage is AC100-277V, each led temporary work light comes with 10ft 18/3 cord.									
Connection Way:	60W, same power	100W, same power	150W, same power						
The maximum quantity for fixture's plug to link another fixture's socket, without power cord	10 pieces	6 pieces	4 pieces						

APPLICATION

- * New Building Construction or Renovation.
- * Maintenance or storage spaces in commercial or institutional facilitate.
- * Short-term maintenance projects.
- * Warehouses, factories, Exhibition halls and workshops.
- * Highway toll stations and gas stations.







